





FEATURERS



Fast pull down

Real air-forced cooling system



Super large space

1006-liter (35.5 cu.ft) space, more storage



Suction circulation system

Big fans for better temp uniformity




Universal castor wheels

Castors with brake & leveling feet



Lockable doors

2 Standard locks with keys for 3 doors



MPC-5V1006A PULL DOWN TEST



High quality steel material

Antibacterial and corrosion resistant



Precise temp. control

Temp. control accurate to 0.1°C



5 types of alarm

Audible and visual alarms




Variable space


Height adjustable shelves





Eco-friendly

CFC-free refrigerant and energy-saving













Real forced air circulation and excellent refrigeration system pull down the chamber temperature rapidly and keep the chamber with good temperature uniformity and fluctuation.

PARAMETER

Performance		Refrigeration System		Alarms	
Cooling method	Forced Air Cooling	Refrigerant	R600a	High/low temperature	Υ
Defrost	Auto	Temp. controller	Microprocessor	Power failure	Υ
Shelf/drawer	Shelves/10	Sensor	NTC	Sensor error	Υ
Temperature range	2°C~8°C	Display	Digital display	Controller failure	Υ
Ambient temperature	10~32℃	External material	Sprayed steel	Door ajar	Υ
Noise (db)	53	Compressor QTY	1	Power failure backup	8 hours
Electrical Data		Dimensions		Other	
Voltage frequency(V/Hz)	220V 50Hz	Package size(W*D*H)(mm)	1335*945*2000	Inside door	10 shelves
Power (W)	302W	Capacity (L/cu.ft)	1006/35.5	Remote alarm port	Optional
Current (A)	2.4A	Exterior size(W*D*H)(mm)	1220*865*1885	Access port QTY/Dia.	1/25mm
Power consumption	4.23kWh/24h	Interior size(W*D*H)(mm)	1100*684*1325	Internal material	SUS 304